







Robot-specific pneumatic polishing tool

| Model | ZD-4350 | ZD-4375 | ZD-3500 | ZD-4500 | ZD-5500 | ZD-75100 | ZD-75145 |
|--------------------|---|---|---|---|--|---|---|
| pic |  |  |  |  |  |  |  |
| Specifications | 50m | 75m | 75m | 100m | 125m | 100*75mm | 145*75mm |
| Weight | 700g | 700g | 1100g | 1100g | 1100g | 1100g | 1200g |
| Air consumption | 380L/min | 380L/min | 380L/min | 380L/min | 380L/min | 380L/min | 380L/分 |
| Operating pressure | 6.0Kg/cm ² | 6.0Kg/cm ² | 6.0Kg/cm ² | 6.0Kg/cm ² | 6.0Kg/cm ² | 6.0Kg/cm ² | 6.0Kg/cm ² |
| Noise level | 60dBa | 60dBa | 60dBa | 60dBa | 60dBa | 60dBa | 60dBa |
| Power | 240W | 240W | 240W | 240W | 240W | 240W | 240W |
| Rotation speed | 2500RPM | 2500RPM | 12000RPM | 12000RPM | 12000RPM | 10000RPM | 10000RPM |
| Eccentricity | concentric | concentric | 5mm | 5mm | 5mm | 3mm | 3mm |
| Pallet | 50mm | 75mm | 75mm | 100mm | 125mm | 100*75mm | 145*75mm |

| Model | ZD-4250 | ZD-4275 | ZD-2500ZB |
|--------------------|---|---|---|
| pic |  |  |  |
| Specifications | 50mm | 75mm | 50-125mm |
| Weight | 700g | 700g | 1100g |
| Air consumption | 380L/ min | 380L/min | 380L/min |
| Operating pressure | 6. 0Kg/cm ² | 6. 0Kg/cm ² | 6. 0Kg/cm ² |
| Noise level | 60dBa | 60dBa | 60dBa |
| Power | 240W | 240W | 240W |
| Rotation speed | 15000 RPM | 15000 RPM | 2500 RPM |
| Eccentricity | 3mm | 3mm | concentric |
| Pallet | 50mm | 75mm | 50-125mm |

For angular misalignment: Suitable for objects with relatively flat surfaces.

For concentric (without angular misalignment): Suitable for applications requiring greater cutting force, deburring, and chamfering.